

DEVILBISS®

JJ

Air Spray Gun



DEVILBISS



Air Spray Gun

“Fit & Feel”

Available in gravity, suction and pressure feed type

Super Light Weight, Compact & Easy Operation
High Performance Spray Gun featuring Finest Atomization

● **Super Light Weight, Compact & Easy Operation**

JJ gun is built at super light weight of 330g featuring finest atomization. It provides a quality finish with both metallic & pearl paints.

● **Stainless Steel Fluid Passage**

The fluid passage is made of stainless steel, compatible with all types of paints including waterborne.

● **Air Cap for the Finest Atomization**

Perfect alignment between the air cap and the fluid tip is maintained through DeVilbiss' patented Ball & Cone principle and therefore it provides excellent atomization as well as consistent and uniform spray patterns.

● **Low Trigger Pull**

Due to unique design of the air valve, the trigger pull force is constant, even with high input pressures. It provides the trigger pull with only 1.5kg and this allows users to spray for a longer time without having stress.

● **Plated Gun Body**

For a harder, durable finish and ease of cleaning, plated gun body is employed.

Selection of Air Cap, Fluid Tip and Gun Type

• For your ordering reference :

JJ

Air Cap No.

Tip Size

S: Suction Type
G: Gravity Type
P: Pressure Type

(Example) **JJ - 243 - 1.3 - G**

Pressure type: LVMP

Low Volume Medium Pressure

**HIGH TRANSFER
EFFICIENCY**

**FINE
ATOMIZATION**

**LOW AIR
CONSUMPTION**

Comparing the existing Air Spray Gun or HVLP gun, LVMP gun makes higher transfer efficiency and better atomization possible with less air consumption.

Specifications

Air Cap	Type	Tip Size (mm)					Air Consumption (Air Inlet Pressure)	Pattern Range	Air Inlet	Fluid Inlet	Weight	Features & Applications
		0.8	1.0	1.3	1.5	1.8						
203	G(Gravity)	○					80 ℓ /min (0.1MPa)	100mm	G 1/4	G 1/4	330g	Low volume, spot touch-up
243	G(Gravity)		○	○	○	○	220 ℓ /min (0.2MPa)	250mm	G 1/4	G 1/4	330g	Mid-high volume, fine atomization, autorefinishing wood & metal finishing
	S(Suction)			○	○	○						
205	P(Pressure)	○	○	○			200 ℓ /min (0.2MPa)	250mm	G 1/4	G 1/4	330g	LVMP, Low-high volume, fine atomization, autorefinishing wood & metal finishing
207	P(Pressure)	○	○	○				300mm				

Accessories

- KGP-4 Gravity Cup (400 ml, resin light weight cup)
- KR-470-2 Suction Cup (700 ml)
- KG-400 Gravity Cup (400 ml)
- KG-400-T Gravity Cup (400 ml, Teflon-coated)

- KG-250 Gravity Cup (250 ml)
- HAV-501-B Air Inlet Control Valve and Gauge
- HAF-507 Disposable Air Filter
- SSL-10 Spray Gun Lube (60 ml)

※ Delrin and Teflon are both registered marks of E.I.Du Pont de Nemours and Company.

※ For improvement purposes, Design & Specifications may change without prior notice.

北京悦友信达涂装设备有限公司

联系电话：010-82905966 传真：010-82905966

手机：13521622487

网址：http://www.bjyyxd.com.cn, Email: hbhyd@163.com

地址：北京市海淀区清河三旗东路，邮编：100096

代理/經銷商：